1/4"-4" POLYPROPYLENE

FEATURES

- Stainless steel rings, arms and pins
- Versatile interchangeable with all types of cam lever couplings
- Precision molded ensures a uniform and accurate fit
- Durable polypropylene is glass reinforced for rugged strength
- Smooth operating finger rings are designed for easy opening of cam levers
- Economical and superior in performance
- Where noted, parts must be ordered in bag quantities
- ¼" and ½" series couplings interchange with ¾" size couplings. Coupling ends are ¾" size.
- 1¼" series couplings interchange with 1" size couplings. Coupling ends are 1" size.
- 1½" x 1¼" couplings interchange with 1½" size couplings. Coupling ends are 1½" size.



	POLYPROPYLENE CAM LEVER COUPLINGS												
ITEM	DESCRIPTION	1/4"	1/2"	3/4"	1"	11/4"	1½" x 1¼"	11/2"	2"	21/2"	3"	3" 3 ARMS	4" 3 ARMS
Α	MALE ADAPTER X FEMALE THREAD	75A1/4	75A1/2	75A3/4	100A	125A	150125A	150A	200A		300A		400A
В	FEMALE COUPLER X MALE THREAD		75B1/2	75B3/4	100B	125B	150125B	150B	200B		300B	303B	400B
С	FEMALE COUPLER X HOSE BARB		050C	075C	100C	125C	150125C	150C	200C		300C	303C	400C
D	FEMALE COUPLER X FEMALE THREAD		050D	075D	100D	125D	150125D	150D	200D		300D		400D
Е	MALE ADAPTER X HOSE BARB		050E	075E	100E	125E	150125E	150E	200E		300E		400E
F	MALE ADAPTER X MALE THREAD		050F	075F	100F	125F	150125F	150F	200F		300F		400F
PL	PLUG FOR FEMALE COUPLER		75PL	75PL	100125PL	100125PL	150PL	150PL	200PL		300PL		400PL
CAP	CAP FOR MALE ADAPTER		075CAP	075CAP	100125CAP	100125CAP	150CAP	150CAP	200CAP	250CAP	300CAP		400CAP (2 arms)
CAPSH	CAP WITH SHORT ARMS						200CAPSH						



WARNING! Couplings should not be disconnected under pressure or with liquid in the line.

1/4" SERIES POLY CAM LEVER COUPLINGS							
PART NO	DESCRIPTION	MAX PSI	GASKET	LOT QTY			
75A1/4	$^3\!\!4$ " MALE ADAPTER X $^1\!\!4$ " FEMALE THREAD	300	N/A	10/BAG			

	½" SERIES POLY CAM LEVER COUPLINGS						
PART NO	DESCRIPTION	MAX PSI	GASKET	LOT QTY			
75A1/2	¾" MALE ADAPTER X ½" FEMALE THREAD	225	N/A	10/BAG			
75B1/2	¾" FEMALE COUPLER X ½" MALE THREAD	300	EPDM	10/BAG			
050C	¾" FEMALE COUPLER X ½" HOSE BARB	300	EPDM	10/BAG			
050D	³ ⁄ ₄ " FEMALE COUPLER X ¹ ⁄ ₂ " FEMALE THREAD	300	EPDM	10/BAG			
050E	¾" MALE ADAPTER X ½" HOSE BARB	300	N/A	10/BAG			
050F	¾" MALE ADAPTER X ½" MALE THREAD	300	N/A	10/BAG			
075CAP	¾" CAP X MALE ADAPTER	300	EPDM	10/BAG			
75PL	3/4" PLUG X FEMALE COUPLER	300	N/A	10/BAG			



3/4" SERIES POLY CAM LEVER COUPLINGS						
PART NO	DESCRIPTION	MAX PSI	GASKET	LOT QTY		
75A3/4	3/4" MALE ADAPTER X 3/4" FEMALE THREAD	225	N/A	10/BAG		
75B3/4	3/4" FEMALE COUPLER X 3/4" MALE THREAD	300	EPDM	10/BAG		
075C	3/4" FEMALE COUPLER X 3/4" HOSE BARB	300	EPDM	10/BAG		
075D	3/4" FEMALE COUPLER X 3/4" FEMALE THREAD	300	EPDM	10/BAG		
075E	¾" MALE ADAPTER X ¾" HOSE BARB	300	N/A	10/BAG		
075F	3/4" MALE ADAPTER X 3/4" MALE THREAD	300	N/A	10/BAG		
075CAP	3/4" CAP X MALE ADAPTER	300	EPDM	10/BAG		
75PL	3/4" PLUG X FEMALE COUPLER	300	N/A	10/BAG		

1" SERIES POLY CAM LEVER COUPLINGS						
PART NO	DESCRIPTION	MAX PSI	GASKET	LOT QTY		
100A	1" MALE ADAPTER X 1" FEMALE THREAD	300	N/A	10/BAG		
100B	1" FEMALE COUPLER X 1" MALE THREAD	300	EPDM	10/BAG		
100C	1" FEMALE COUPLER X 1" HOSE BARB	300	EPDM	10/BAG		
100D	1" FEMALE COUPLER X 1" FEMALE THREAD	300	EPDM	10/BAG		
100E	1" MALE ADAPTER X 1" HOSE BARB	300	N/A	10/BAG		
100F	1" MALE ADAPTER X 1" MALE THREAD	300	N/A	10/BAG		
100125CAP	1" CAP X MALE ADAPTER	300	EPDM	10/BAG		
100125PL	1" PLUG X FEMALE COUPLER	300	N/A	10/BAG		

	11/4" SERIES POLY CAM LEVER COUPLINGS						
PART NO	DESCRIPTION	MAX PSI	GASKET	LOT QTY			
125A	1" MALE ADAPTER X 11/4" FEMALE THREAD	300	N/A	10/BAG			
125B	1" FEMALE COUPLER X 11/4" MALE THREAD	300	EPDM	10/BAG			
125C	1" FEMALE COUPLER X 11/4" HOSE BARB	300	EPDM	10/BAG			
125D	1" FEMALE COUPLER X 11/4" FEMALE THREAD	300	EPDM	10/BAG			
125E	1" MALE ADAPTER X 11/4" HOSE BARB	300	N/A	10/BAG			
125F	1" MALE ADAPTER X 11/4" MALE THREAD	300	N/A	10/BAG			
100125CAP	1" CAP X MALE ADAPTER	300	EPDM	10/BAG			
100125PL	1" PLUG X FEMALE COUPLER	300	N/A	10/BAG			

11/2	1½" X 1¼" SERIES POLY CAM LEVER COUPLINGS						
PART NO	DESCRIPTION	MAX PSI	GASKET	LOT QTY			
150125A	1½" MALE ADAPTER X 1¼" FEMALE THREAD	225	N/A	10/BAG			
150125B	1½" FEMALE COUPLER X 1¼" MALE THREAD	300	EPDM	10			
150125C	1½" FEMALE COUPLER X 1¼" HOSE BARB	300	EPDM	10			
150125D	1½" FEMALE COUPLER X 1¼" FEMALE THREAD	300	EPDM	10			
150125E	1½" MALE ADAPTER X 1¼" HOSE BARB	225	EPDM	10/BAG			
150125F	1½" MALE ADAPTER X 1¼" MALE THREAD	300	N/A	10/BAG			
150CAP	1½" CAP X MALE ADAPTER	300	EPDM	10			
150PL	1½" PLUG X FEMALE COUPLER	225	N/A	10/BAG			

1½" SERIES POLY CAM LEVER COUPLINGS						
PART NO	DESCRIPTION	MAX PSI	GASKET	LOT QTY		
150A	1½" MALE ADAPTER X 1½" FEMALE THREAD	225	N/A	10/BAG		
150B	1½" FEMALE COUPLER X 1½" MALE THREAD	300	EPDM	10		
150C	1½" FEMALE COUPLER X 1½" HOSE BARB	300	EPDM	10		
150D	1½" FEMALE COUPLER X 1½" FEMALE THREAD	300	EPDM	10		
150E	1½" MALE ADAPTER X 1½" HOSE BARB	200	N/A	10/BAG		
150F	1½" MALE ADAPTER X 1½" MALE THREAD	300	N/A	10/BAG		
150CAP	1½" CAP X MALE ADAPTER	300	EPDM	10		
150PL	1½" PLUG X FEMALE COUPLER	225	N/A	10/BAG		

1/4"-4" POLYPROPYLENE

FEATURES

- Stainless steel rings, arms and pins
- Versatile interchangeable with all types of cam lever couplings
- Precision molded ensures a uniform and accurate fit
- Durable polypropylene is glass reinforced for rugged strength
- Smooth operating finger rings are designed for easy opening of cam levers
- Economical and superior in performance
- Standard with EPDM gaskets, FKM gaskets can be ordered separately on page 79
- Where noted, parts must be ordered in bag quantities
- ¼",¾" and ½" series couplings interchange with ¾" size couplings. Coupling ends are ¾" size.
- 1¼" series couplings interchange with 1" size couplings. Coupling ends are 1" size.
- 1½" x 1¼" couplings interchange with 1½" size couplings. Coupling ends are 1½" size.



WARNING! Couplings should not be disconnected under pressure or with liquid in the line.



1/4"-4" POLYPROPYLENE

FEATURES

- Stainless steel rings, arms and pins
- Versatile interchangeable with all types of cam lever couplings
- Precision molded ensures a uniform and accurate fit
- Durable polypropylene is glass reinforced for rugged strength
- Smooth operating finger rings are designed for easy opening of cam levers
- Economical and superior in performance
- Where noted, parts must be ordered in bag quantities
- ¼",¾" and ½" series couplings interchange with ¾" size couplings. Coupling ends are ¾" size.
- 1¼" series couplings interchange with 1" size couplings. Coupling ends are 1" size.
- 1½" x 1¼" couplings interchange with 1½" size couplings. Coupling ends are 1½" size.



WARNING! Couplings should not be disconnected under pressure or with liquid in the line.



	2" SERIES POLY CAM LEVER COUPLINGS							
PART NO	DESCRIPTION	MAX PSI	GASKET	LOT QTY				
200A	2" MALE ADAPTER X 2" FEMALE THREAD	225	N/A	10/BAG				
200B	2" FEMALE COUPLER X 2" MALE THREAD	225	EPDM	20				
201B	2" FEMALE COUPLER X 2" EXTENDED MALE THREAD	200	EPDM	10				
200C	2" FEMALE COUPLER X 2" HOSE BARB	225	EPDM	20				
200D	2" FEMALE COUPLER X 2" FEMALE THREAD	200	EPDM	20				
200E	2" MALE ADAPTER X 2" HOSE BARB	200	N/A	10/BAG				
200F	2" MALE ADAPTER X 2" MALE THREAD	300	N/A	10/BAG				
200CAP	2" CAP X MALE ADAPTER	200	EPDM	20				
200CAPSH	2" CAP X MALE ADAPTER W/SHORT ARMS	200	EPDM	10				
200PL	2" PLUG X FEMALE COUPLER	225	N/A	10/BAG				

2"	2" X 1½" SERIES POLY CAM LEVER COUPLINGS							
PART NO	DESCRIPTION	MAX PSI	GASKET	LOT QTY				
200150C	2" FEMALE COUPLER X 1½" HOSE BARB	300	EPDM	10				

21/2" SERIES POLY CAM LEVER COUPLINGS						
PART NO	DESCRIPTION	MAX PSI	GASKET	QTY		
250CAP	2½" CAP X MALE ADAPTER	300	EPDM	1		



3" SERIES POLY CAM LEVER COUPLINGS						
PART NO	DESCRIPTION	MAX PSI	GASKET	LOT QTY		
300A	3" MALE ADAPTER X 3" FEMALE THREAD	100	N/A	10		
300B	3" FEMALE COUPLER X 3" MALE THREAD	150	EPDM	10		
303B	3" FEMALE COUPLER X 3" EXTENDED MALE THREAD	200	EPDM	10		
303B200A	3" FEMALE COUPLER W/ 3 ARMS X 2" MALE ADAPTER	200	EPDM	10		
300C	3" FEMALE COUPLER X 3" HOSE BARB	200	EPDM	10		
303C	3" FEMALE COUPLER W/ 3 ARMS X 3" HOSE BARB	200	EPDM	10		
300D	3" FEMALE COUPLER X 3" FEMALE THREAD	200	EPDM	10		
300E	3" MALE ADAPTER X 3" HOSE BARB	150	N/A	10		
300F	3" MALE ADAPTER X 3" MALE THREAD	100	N/A	10		
300CAP	3" CAP X MALE ADAPTER	100	EPDM	10		
300PL	3" PLUG X FEMALE COUPLER	150	N/A	10		

4" SERIES POLY CAM LEVER COUPLINGS				
PART NO	DESCRIPTION	MAX PSI	GASKET	LOT QTY
400A	4" MALE ADAPTER X 4" FEMALE THREAD	75	N/A	10
400B	4" FEMALE COUPLER X 4" MALE THREAD	150	EPDM	10
400C	4" FEMALE COUPLER X 4" HOSE BARB	150	EPDM	10
400D	4" FEMALE COUPLER X 4" FEMALE THREAD	100	EPDM	10
400E	4" MALE ADAPTER X 4" HOSE BARB	50	N/A	10
400F	4" MALE ADAPTER X 4" MALE THREAD	75	N/A	10
400CAP	4" CAP X MALE ADAPTER (W/2 ARMS)	100	EPDM	10
400PL	4" PLUG X FEMALE COUPLER	75	N/A	10

EASY ACTION LOCKING LEVER!




11/2"- 2" SERIES LOCKING POLY CAM LEVER COUPLINGS				
PART NO	DESCRIPTION	MAX PSI	GASKET	QTY
L200B	2" FEMALE COUPLER X 2" MALE THREAD	225	EPDM	1
L200C	2" FEMALE COUPLER X 2" HOSE BARB	225	EPDM	1
L200D	2" FEMALE COUPLER X 2" FEMALE THREAD	200	EPDM	1
L200CAP	2" CAP X MALE ADAPTER	200	EPDM	1



SPOOL ADAPTERS				
PART NO	DESCRIPTION	MAX PSI	GASKET	LOT QTY
200FF	2" MALE ADAPTER X 2" MALE ADAPTER	150	N/A	10/BAG
300F200F	3" MALE ADAPTER X 2" MALE ADAPTER	75	N/A	10
300FF	3" MALE ADAPTER X 3" MALE ADAPTER	75	N/A	10







REPLACEMENT PARTS				
PART NO	DESCRIPTION	LOT QTY		
100RING	RING FITS ¾" & 1"	1		
150RING	RING FITS 11/2", 2", 3", 4"	1		
150(200)K	11/2", 2" SS CAM ARM W/RING	1		
300K	3" SS CAM ARM WITH RING	1		
V20207	11" LANYARD	1		
75G	$\frac{1}{2}$ " & $\frac{3}{4}$ " EPDM GASKET	25		
100G	1" & 11/4" EPDM GASKET	25		
100GV	1" & 11/4" FKM GASKET	25		
150G	1½" EPDM GASKET	25		
150GV	1½" FKM GASKET	25		
200G	2" EPDM GASKET	25		
200GV	2" FKM GASKET	25		
300G	3" EPDM GASKET	25		
300GV	3" FKM GASKET	25		
400G	4" EPDM GASKET	1		
200KL	2" LOCKING CAM ARM WITH RING FITS 11/2" & 2"	1		
200PKL	2" COUPLING PIN FITS 1½" & 2"	1		
200P	2" COUPLING PIN	1		
300P	3" COUPLING PIN	1		

1/4"-4" POLYPROPYLENE

FEATURES

- Chemical resistant to protect against corrosion
- Versatile to interchange with all types of cam lever couplings
- Smooth operation makes connections quick and easy
- Where noted, parts must be ordered in bag quantities
- Locking cam arm lever is not intended to be used as a security device or prevent unauthorized opening of coupling assembly.



WARNING! Couplings should not be disconnected under pressure or with liquid in the line.

1½"-2" 90° & 45° POLYPROPYLENE

FEATURES

- Precision molded in polypropylene, reinforced with fiberglass for strength
- Stainless steel rings, arms and pins resist corrosion
- 90° angle couplings and adapters will reduce the number of elbows and other pipe fittings used in plumbing applications



WARNING! Couplings should not be disconnected under pressure or with liquid in the line.



1½" 90° POLY CAM LEVER COUPLINGS					
PART NO	DESCRIPTION	MAX PSI	GASKET	LOT QTY	
150A90	1½" 90° MALE ADAPTER X 1½" FEMALE THREAD	225	N/A	10/BAG	
150C90	1½" 90° FEMALE COUPLER X 1½" HOSE BARB	225	EPDM	10	
150D90	1½" 90° FEMALE COUPLER X 1½" FEMALE THREAD	300	EPDM	10	
150F90	1½" 90° MALE ADAPTER X 1½" MALE THREAD	300	N/A	10/BAG	

2" 90° SERIES POLY CAM LEVER COUPLINGS				
PART NO	DESCRIPTION	MAX PSI	GASKET	LOT QTY
200A90	2" 90° MALE ADAPTER X 2" FEMALE THREAD	225	N/A	10/BAG
200B90	2" 90° FEMALE COUPLER X 2" MALE THREAD	225	EPDM	10
200C90	2" 90° FEMALE COUPLER X 2" HOSE BARB	225	EPDM	10
200D90	2" 90° FEMALE COUPLER X 2" FEMALE THREAD	200	EPDM	10
200F90	2" 90° MALE ADAPTER X 2" MALE THREAD	225	N/A	10/BAG

2" 45° POLY CAM LEVER COUPLINGS					
PART NO	DESCRIPTION	MAX PSI	GASKET	LOT QTY	
200F45	2" 45° MALE ADAPTER X 2" MALE THREAD	225	N/A	10/BAG	



10/BAG

10/BAG

10/BAG

25

300

300

300

N/A

GARDEN HOSE FITTINGS

FEATURES

- Same construction and design that farmers use for their heavy spraying applications.
- Rugged, secure quick-connect cam arms
- Heavy-duty thick wall reinforced polypropylene
- Proven, leak-free construction
- Full flow design



34" MALE NPT X 34" GARDEN HOSE FEMALE THREAD

3/4" FEMALE NPT X 3/4" GARDEN HOSE MALE THREAD

 $^3\!\!4$ " MALE NPT X $^3\!\!4$ " GARDEN HOSE MALE THREAD

3/4" GARDEN HOSE FITTING GASKET

GHFT075MPT

GHMT075FPT

GHMT075MPT

GHFT075G



Spray nozzle patterns

GARDEN HOSE NOZZLE

FEATURES

- Heavy duty machined aluminum construction stands up to hard use
- · Comfort grip soft rubber
- Resists dents, mars and scratches; protects any surface that comes in contact with nozzle
- Aluminum hose connection provides a tight fit, will not rust
- Multiple spray pattern adjusts from a powerful jet stream to a gentle fan spray. Ideal for all your spraying needs.
- Stainless steel spray cap for precise spray patterns

